

TECHNICAL STUDY OF PROJECTS (Ceiling and special hoods)

Ed.:v20.3

| | | | | |
|-----------------------------|--|----------------|---------------|-------------|
| CUSTOMER: | | | | |
| MODEL, SIZE Y MOTOR: | | | | |
| Po N° or BUDGET: | | CEILING | ISLAND | WALL |

Further to your Purchase order, we kindly request you to fulfil the captioned technical Form and submit back e-mail com.pando@pando.es , or fax al +34 937579653.
This document intends to offer the best technical assessment in order to verify the model compatibility and selected hood version for your Project.

SMOKE EXIT DUCTING

| | | | |
|---|--|--|--------------------------------------|
| Distance between false ceiling and concrete ceiling (cm): | | | Side for ducting exit , Side N° |
| Ducting Diameter Ø (mm):..... | | | Side 1: Upper side |
| In-line straight ducting distance (m):..... | | | Side 2: Short left side |
| Vertical In-Line ducting distance (m):..... | | | Side 3: Long side (front) |
| N° of bends and degrees along ducting:.. | | Image showing ceiling hood frontal part (3), door/panel opening direction. | |

The device to place at the end of the ductwork (exit) has to be adequate to prevent from sever airflow loose Please check the Pando accessory List (Latest Catalogue) (Backdraft shutters, Windows and vents section).

For a fine performance the room must have a continuous air intake admission from the outside

COOKTOP ZONE STUDY

| | | |
|--|--|------------------------|
| Height from cooktop to the hood filters (cm): | | COOKTOP DRAWING |
| Description and sizes of cooktop elements, drawing (cm): (Induction, Gas, Vitro, Teppan Yaki, Wok, Grill, Freidora...) (50x50 + 50x50 + 35x50 + 40x50 + 90x35...) | | |

For a fine performance cooktop must be totally centred below the hood

Air streams affecting the cooktop zone, must be avoided at all times

EXTRACTOR HOOD SECTION WITH REMOTE MOTOR: Ducting intake and motor exit

| | |
|--|--|
| In-Line ducting distance between hood and remote motor intake (m) :..... | |
| In-Line ducting distance between remote motor and final exit (m) :.. | |

For maintenance purposes, remote motor must show easy access to Customer Service

| | | | | | | | |
|-----------------|-------|--|---------|--|----------------------------------|--|----------------------|
| Type of Kitchen | OPEN: | | CLOSED: | | HEIGHT from floor to ceiling(m): | | Optional, square m²: |
|-----------------|-------|--|---------|--|----------------------------------|--|----------------------|

INSTALLATION GLOBAL DRAWING (Hood, cooktop/ worktop y and ducting layout)

NOTES

| | | | | | | | | |
|------------------|----------|--|-------|--|-----------|--|---------|--|
| Inoxpan cheking: | STUDY N° | | DATE: | | TECHNICAL | | OUTCOME | |
|------------------|----------|--|-------|--|-----------|--|---------|--|

Inoxpan.S.L. shall not prove to be liable of a fine product performance if fitting, use and maintenance instructions are not followed, according to what shown in the User's Manual included along with the product. This current technical Study has only advisory goals for a fine election of the right model and appropriated installation. .